



LOW BAY

SURFACE / SUSPENDED
IP54 / IK08




Polycarbonate (PC) 3mm thickness
IK08



Bright diffuse aluminium with 97%
total reflectance

drawing #1



Net lumen output	CCT	Power	Wiring	Dimensions	Weight	ACS	Purchase code
(lm)	(K)	(W)		(mm)	(kg)	#	
15 000	3000	121	ECG	drawing #1	8.00	N/A	LBS/P-121-15000/4.3/IP54AL/P5W
16 000	4000	121	ECG	drawing #1	8.00	N/A	LBS/P-121-16000/4.4/IP54AL/P5W

LOW BAY



5 years warranty

50,000 hrs
L80/B10
Ta=25°C

220-240V
50-60Hz



Low Bay

Low Bay
Surface / Suspended

LIGHT OUTPUT	up to 16 000 lm
EFFICIENCY	up to 132 lm/W
WIRING	ECG, on request: DALI On request: Emergency kit (1h, 3h)
CCT	3000 - 4000K
CRI	≥ 80 Ra
MATERIALS	
> Housing	Sheet steel
> Diffuser	Polycarbonate (PC) 3mm thickness
> Reflector	Bright diffuse aluminium with 97% total reflectance
LIGHT DISTRIBUTION	Direct
ADVANTAGES	Impact-resistant (IK08)
SURFACE FINISH	White color (RAL9003); other colors on request
ACCESSORIES	N/A