



# Chrisy

by Mareli





## MARELI LTD

57 Tsaritsa Yonna blvd., Lulin 7  
1324 Sofia, Bulgaria  
00359 2 4260 906  
00359 882 650 200  
sales@mareli-bg.com  
www.mareli-bg.com



Sealed with polyurethane gasket to improve IP65 protection.  
Special screws grip frame to the housing covered with elegant plastic plugs



All models are Supplied with feeding cable



5 years warranty | 50,000 hrs lifespan | 220-240V 50-60Hz |

Chrysy	Chrysy Recessed Opal Glass	Chrysy Recessed Opal PMMA	Chrysy Recessed Microprismatic
<b>LIGHT OUTPUT</b>	up to 5300 lm	up to 6000 lm	up to 6500 lm
<b>EFFICIENCY</b>	up to 104 lm/W	up to 118 lm/W	up to 127 lm/W
<b>WIRING</b>	ECG, on request: DALI, 1-10V On request: Emergency kit (1h, 3h)	ECG, on request: DALI, 1-10V On request: Emergency kit (1h, 3h)	ECG, on request: DALI, 1-10V On request: Emergency kit (1h, 3h)
<b>CCT</b>	3000 - 4000K	3000 - 4000K	3000 - 4000K
<b>CRI</b>	≥ 80 Ra	≥ 80 Ra	≥ 80 Ra
<b>MATERIALS</b>			
> Housing	Sheet steel	Sheet steel	Sheet steel
> Frame	Extruded aluminium profile	Extruded aluminium profile	Extruded aluminium profile
> Diffuser	Opal Glass	Opal PMMA Mat Pattern	Opal Microprismatic
<b>LIGHT DISTRIBUTION</b>	Direct	Direct	Direct
<b>SURFACE FINISH</b>	White color (RAL9003); other colors on request	White color (RAL9003); other colors on request	White color (RAL9003); other colors on request
<b>ACCESSORIES</b>	N/A	N/A	N/A



Opal Glass




Opal PMMA Mat Pattern



Microprismatic



# Chrysy

Opal Glass  
Recessed




# Chrysy

Opal PMMA  
Recessed




5 years warranty | 50,000 hrs lifespan | 220-240V 50-60Hz |




5 years warranty | 50,000 hrs lifespan | 220-240V 50-60Hz |

## Chrysy Opal Glass, All models

drawing #1



drawing #2




Net lumen output	CCT	Power	Wiring	Dimensions	Weight	Purchase code
(lm)	(K)	(W)		(mm)	(kg)	
3600	3000	36	STD	drawing #1	6.00	ChrRE594-36-3600/6.3/IP65OGW+cable
3800	4000	36	STD	drawing #1	6.00	ChrRE594-36-3800/6.4/IP65OGW+cable
5000	3000	51	STD	drawing #1	6.00	ChrRE594-51-5000/6.3/IP65OGW+cable
5300	4000	51	STD	drawing #1	6.00	ChrRE594-51-5300/6.4/IP65OGW+cable
Ceiling standard 625x625mm						
3600	3000	36	STD	drawing #2	6.10	ChrRG620-36-3600/6.3/IP65OGW+cable
3800	4000	36	STD	drawing #2	6.10	ChrRG620-36-3800/6.4/IP65OGW+cable
5000	3000	51	STD	drawing #2	6.10	ChrRG620-51-5000/6.3/IP65OGW+cable
5300	4000	51	STD	drawing #2	6.10	ChrRG620-51-5300/6.4/IP65OGW+cable

#	Accessories (ACS)	Purchase code
#	N/A	N/A


STD - Standard driver  
DALI, 1-10V available on request  
Emergency kit (1h or 3h) available on request

## Chrysy Opal PMMA, All models

drawing #1



drawing #2



Net lumen output	CCT	Power	Wiring	Dimensions	Weight	Purchase code
(lm)	(K)	(W)		(mm)	(kg)	
4100	3000	36	STD	drawing #1	6.00	ChrRE594-36-4100/6.3/IP65O3W+cable
4300	4000	36	STD	drawing #1	6.00	ChrRE594-36-4300/6.4/IP65O3W+cable
5700	3000	51	STD	drawing #1	6.00	ChrRE594-51-5700/6.3/IP65O3W+cable
6000	4000	51	STD	drawing #1	6.00	ChrRE594-51-6000/6.4/IP65O3W+cable
Ceiling standard 625x625mm						
4100	3000	36	STD	drawing #2	6.10	ChrRG620-36-4100/6.3/IP65O3W+cable
4300	4000	36	STD	drawing #2	6.10	ChrRG620-36-4300/6.4/IP65O3W+cable
5700	3000	51	STD	drawing #2	6.10	ChrRG620-51-5700/6.3/IP65O3W+cable
6000	4000	51	STD	drawing #2	6.10	ChrRG620-51-6000/6.4/IP65O3W+cable


#	Accessories (ACS)	Purchase code
#	N/A	N/A

STD - Standard driver  
DALI, 1-10V available on request  
Emergency kit (1h or 3h) available on request



# Chrisy

Microprismatic  
Recessed



LED


IP65

ECG DALI

ECG 1-10V


EMERGENCY

5 years warranty | 50,000 hrs lifespan | 220-240V 50-60Hz





## Chrisy Microprismatic, All models

drawing #1



drawing #2



Net lumen output	CCT	Power	Wiring	Dimensions	Weight	Purchase code
(lm)	(K)	(W)		(mm)	(kg)	
4400	3000	36	STD	drawing #1	6.00	ChrRE594-36-4400/6.3/IP65P3W+cable
4700	4000	36	STD	drawing #1	6.00	ChrRE594-36-4700/6.4/IP65P3W+cable
6200	3000	51	STD	drawing #1	6.00	ChrRE594-51-6200/6.3/IP65P3W+cable
6500	4000	51	STD	drawing #1	6.00	ChrRE594-51-6500/6.4/IP65P3W+cable
Ceiling standard 625x625mm						
4400	3000	36	STD	drawing #2	6.10	ChrRG620-36-4400/6.3/IP65P3W+cable
4700	4000	36	STD	drawing #2	6.10	ChrREG620-36-4700/6.4/IP65P3W+cable
6200	3000	51	STD	drawing #2	6.10	ChrRG620-51-6200/6.3/IP65P3W+cable
6500	4000	51	STD	drawing #2	6.10	ChrRG620-51-6500/6.4/IP65P3W+cable

#	Accessories (ACS)	Purchase code
#	N/A	N/A

STD - Standard driver  
 DALI, 1-10V available on request  
 Emergency kit (1h or 3h) available on request



Mareli Ltd. reserves the right to introduce structural changes and modify the luminaires. Luminous flux and connected electrical load are subject to an initial tolerance of +/- 5%. Tolerance of color temperature: +/-150 K. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Mareli Ltd. reserves the right to introduce structural changes and modify the luminaires. Luminous flux and connected electrical load are subject to an initial tolerance of +/- 5%. Tolerance of color temperature: +/-150 K. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

**THANK YOU!**

FOR ADDITIONAL INFORMATION  
INQUIRIES, ORDERS  
[sales@mareli-bg.com](mailto:sales@mareli-bg.com)  
[www.mareli-bg.com](http://www.mareli-bg.com)

MARELI Ltd 2017