



HIGH BAY

SUSPENDED
IP65 / IK08



LED			IP65	IK08			5 years warranty	50,000 hrs L80/B10 Ta=25°C	220-240V 50-60Hz		CE
-----	--	--	------	------	--	--	------------------	----------------------------------	---------------------	--	----

High Bay	High Bay Small Suspended	High Bay Large Suspended
LIGHT OUTPUT	up to 16 300 lm	up to 32 600 lm
EFFICIENCY	up to 138 lm/W	up to 138 lm/W
WIRING	ECG, on request: DALI On request: Emergency kit (1h, 3h)	ECG, on request: DALI, 1-10V On request: Emergency kit (1h, 3h)
CCT	3000 - 4000K	3000 - 4000K
CRI	≥ 80 Ra	≥ 80 Ra
MATERIALS		
> Housing	Sheet steel	Sheet steel
> Diffuser	Tempered clear glass 5mm thickness, safety hanging	Tempered clear glass 5mm thickness, safety hanging
LIGHT DISTRIBUTION	Direct	Direct
ADVANTAGES	Impact-resistant (IK08), Housing sealed with polyurethane gasket to improve IP65 protection	Impact-resistant (IK08), Housing sealed with polyurethane gasket to improve IP65 protection
SURFACE FINISH	White color (RAL9003); other colors on request	White color (RAL9003); other colors on request
ACCESSORIES	N/A	N/A




Housing sealed with polyurethane gasket to improve IP65 protection




Tempered clear glass 5mm thickness, safety haning IK08



drawing #1



drawing #2



Net lumen output	CCT	Power	Wiring	Dimensions	Weight	ACS	Purchase code
(lm)	(K)	(W)		(mm)	(kg)	#	
31 000	3000	236	ECG	drawing #1	15.00	N/A	HBL4-236-31000/4.3/IP65CGW
32 600	4000	236	ECG	drawing #1	15.00	N/A	HBL4-236-32600/4.4/IP65CGW

**HIGH BAY
LARGE**



Net lumen output	CCT	Power	Wiring	Dimensions	Weight	ACS	Purchase code
(lm)	(K)	(W)		(mm)	(kg)	#	
15 500	3000	118	ECG	drawing #2	8.50	N/A	HBL2-118-15500/4.3/IP65CGW
16 300	4000	118	ECG	drawing #2	8.50	N/A	HBL2-118-16300/4.4/IP65CGW

**HIGH BAY
SMALL**

