



Dary Downlight

Unique from every Angle

Recessed Version

Mareli Ltd




Light in a controlled way

UGR<19; UGR<16 on request*


Changeable Reflector and Lenses

Available Light Distribution Angles:


80° Standart; 50°, 35° and Assymetric on request




80°



50°



35°



Assymmetric

A wide distribution optic range, limited luminance levels and high glare reduction ensure a pleasant sense of light for a maximum visual comfort.

Product Visualisations



Hotel Lobby



Hotel Bedroom

Technical Characteristics

Mareli Ltd.



Product

Name	Dary Downlight
Code	Look at the table on the bottom
Colour	White; Black and Grey others on request
RAL	RAL 9003; RAL 9005; other on request
Mounting	Recessed

Light Source

Type	LED
Efficiency	Up to 155 lm/W
Gross luminous flux	580lm; 850lm; 1150; 1400lm
Colour Temperature	4000 K; 3000K & 5000 K on request
Colour Rendering Index	CRI >80; CRI > 90 on request
Lifetime	Working hours - 80.000 h ; L80B20
Light Beam Angle	80°; 50°,35 and Assymetric on request

Electrical Data

Power	From 4W to 10W
Voltage	220-240V
Warranty	5 years
Dimming	DALI / Push - For other consult it with us
Electrical insulation class	Safety class I

Other technical information

Sealing	IP43
Impact resistance	IK07
Emergency power supply	Please Consult it with us
Ceiling cut out hole	55mm x 295mm
Dimensions	Consult it with us
Packaging dimensions	Consult it with us
Mounting Accessories	Clips included, *Template for ceiling cut-out on request

Purchasing codes

Dary Downlight Recessed 70x308mm-3.8W-580lm/9.4/IP43/*/**/
Dary Downlight Recessed 70x308mm-5.8W-850Lm/9.4/IP43/*/**/
Dary Downlight Recessed 70x308mm-8W-1150Lm/9.4/IP43/*/**/
Dary Downlight Recessed 70x308mm-10W-1400Lm/9.4/IP43/*/**/

colour of optic- white /black/mirror *
 colour of fixture- white/black/grey **



White Reflector with White Body



Mirror Reflector with Grey Body



Black Reflector with Black Body

Drawing

